

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2000-056294

(43)Date of publication of application : 25.02.2000

(51)Int.Cl.

G02F 1/133

(21)Application number : 11-023716

(71)Applicant : SEIKO EPSON CORP

(22)Date of filing : 01.02.1999

(72)Inventor : MAEDA TSUYOSHI

OKAMOTO EIJI

SEKI TAKUMI

OKUMURA OSAMU

(30)Priority



Priority number : 10023656	Priority date : 04.02.1998	Priority country : JP
10096497	08.04.1998	JP
10157622	05.06.1998	JP

(54) LIQUID CRYSTAL DISPLAY DEVICE AND ELECTRONIC EQUIPMENT

(57)Abstract:

PROBLEM TO BE SOLVED: To make an image display with high contrast and high quality both in a reflective display mode and in a transmissive display mode in a liquid crystal display device exchangeable between a reflective display and a transmissive display by suppressing a double image due to parallax and a blot on the display.

SOLUTION: When a backlight 15 is turned on in the dark, as light from a light source passes through a semitransparent reflection plate 7 via a polarizing plate 12 and a phase difference plate 14, and it is guided into a liquid crystal layer 3 to perform a transmissive display. In the sun since an incident external light passing through a polarizing plate 11, a phase difference plate 13 and the liquid crystal layer 3 is reflected on the semitransparent reflection plate 7, a reflective display is performed. A driving voltage is switched correspondingly to either a reflective display mode or a transitive display mode in order to apply a driving voltage most suited to reflectance and transmittance characteristics of the driving voltage to liquid crystal.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application]

converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office